



DL9300

24 WIRE DOT MATRIX PRINTER



- The DL9300 flatbed impact printer is a highly suitable solution for multipart continuous forms and cut sheet (max. eight copies including original), card stock and labels, meeting the full range of teller printing applications. You can print on almost anything.
- Standard APTC (Automatic Paper Thickness Control) and HCPP (Host-Controlled Paper Path) result in easy and fine print jobs, automatically.
- One of the quickest flat-bed impact printers, operating at 360 cps (draft quality, 10 cpi), the DL9300 saves valuable time in the office.
- Enhanced paper handling capability ensures flexibility.

TECHNICAL SPECIFICATIONS

		DL9300
Print technology		24-Dot-Matrix
Max. resolution (HXV)		360 x 360dpi
Print speed	Letter	100cps (10cpi)
	Draft	360cps (10cpi)
Line feed speed		60ms at 6lpi
Paper feed speed		6ips
Command set		Fujitsu DPL24C Plus
Emulation		Epson LQ-1170, IBM Proprinter XL24E
Resident fonts	BITMAP	Courier 10, Pica 10, Prestige Elite 12, Boldface PS, OCR-A, OCR-B, Compression, Correspondence, Draft
	SCALABLE	Timeless, Courier, Nimbus-Sans
Character sets		IBM PC char. sets 1 and 2, IBM PS/2 char. sets (Codepage 437, 850, 851, 852, 855, 860, 862, 863, 865, 866), ISO8859-1/ECMA94 National character sets (USA, UK, German, French, Italian, Spanish, Swedish, Finnish, Norwegian, Danish 1 and 2, Hungarian 1 and 2, Slovenian 1 and 2, Mazowia 1 and 2, PG-DHN, Polish 1 and 2, Latin2 1 and 2, Latin P, ISO-Latin, Kamenicky 1 and 2, Turkish 1 and 2, ELOT927, ELOT928, Cyrillic, Lithuanian 1 and 2, Mik, Macedonian, PG-MAC, ABG, ABY, DEC, GR, Greek11, HBR-DEC and HBR-OLD) Bar code (Codabar, EAN8, EAN13, Code 3 of 9, Industrial 2 of 5, Interleaved 2 of 5, Matrix 2 of 5, UPC type A)
Print width (10 characters/inch)		80 characters, 203.2mm
Paper width	Fan-fold	102mm up to 267mm
	Out-sheet	55mm up to 267mm
Paper feed	Standard	Friction-feed platen, convertible bi-directional tractor on front and rear
	Optional	Single-bin cut sheet feeder for front and/or rear (common part) with envelope capability, convertible bi-directional tractor on front and/or rear (common part)
Copies		Max. 8 including original
Input buffer		Max. 96KB
Interface		Bi-directional Centronics plus RS232C
Weight		12.0kg
Noise level		54dBA
Power requirements		100VAC-120VAC +/- 10%, single-phase, 50/60Hz 220VAC-240VAC + 6% -10%, single-phase, 50/60Hz
Dimensions (H x W x D)		250 x 456 x 300mm
Lifetime	Black Ribbon	5 million characters
	Print head	300 million strokes each pin
MTBF		8000 hours at 25% duty cycle

About Fujitsu

Fujitsu is a full service provider of information technology and communications solutions. Throughout Australia and New Zealand we partner with our customers to consult, design, build, operate and support business solutions. From strategic consulting to application and infrastructure solutions and services, Fujitsu has earned a reputation as the single supplier of choice for leading corporate and government organisations.

Fujitsu Australia Limited ABN
19 001 011 427

Fujitsu Australia Head Office
2 Julius Avenue North Ryde
NSW 2113
Telephone 61 2 9776 4555
Facsimile 61 2 9776 4556

Australian Capital Territory
10 Rudd Street
Canberra ACT 2601
Telephone 61 2 6212 6600
Facsimile 61 2 6257 3798

Northern Territory
79-81 Smith Street
Darwin NT 0800
Telephone 61 8 8943 7700
Facsimile 61 8 8943 7777

Queensland
1 Breakfast Creek Road
Newstead Qld 4006
Telephone 61 7 3119 3200
Facsimile 61 7 3119 3211

South Australia
99 Gawler Place
Adelaide SA 5000
Telephone 61 8 8305 8500
Facsimile 61 8 8305 8555

Victoria
1230 Nepean Highway
Cheltenham Vic 3192
Telephone 61 3 9265 0200
Facsimile 61 3 9265 0500

Western Australia
191 St George's Terrace
Perth WA 6000
Telephone 61 8 9212 5000
Facsimile 61 8 9212 5111

Fujitsu New Zealand Head Office
119-123 Featherston Street
Wellington
Telephone 64 4 495 0700
Facsimile 64 4 495 0730

Auckland
117 Khyber Pass Road
Auckland
Telephone 64 9 356 4800
Facsimile 64 9 356 4851

Christchurch
Unit 2 Amuri Park
Cnr Bealey Avenue and
Churchill Street
Christchurch
Telephone 64 3 353 4260
Facsimile 64 3 363 4134

au.fujitsu.com
nz.fujitsu.com

The Fujitsu logo consists of the word "FUJITSU" in a bold, sans-serif font. Above the letter "I" is a stylized infinity symbol (∞).

THE POSSIBILITIES ARE INFINITE