


SOLID 32E

Investment moderate
Printing costs low

Professional continuous forms laser printing
at price/performance never known before

MICROPLEX®

- **OUTSTANDING LOW COST PER PAGE**
- **MICROPLEX HIGH-END CONTROLLER**
Providing special functions like
 - internal form management
 - n-times format splitting
 - SPS-Control
- **BARCODE-GENERATION**
On-the-fly in the printer



- **SAP + AS/400 COMPATIBLE**
Using PCL 5e+Jetcaps and LAN-IPDS
- **INTERFACES**
USB, Ethernet, parallel IEEE 1284
and serial (RS 232/RS 422)
- **100% PRINT CONTROL**
The Status-Out function gives notice
of each correctly printed page
via interface



600 dpi
32 pages/minute
13,6" print width

MICROPLEX Printware AG

Panzerstraße 5
D-26316 Varel

Mail info@microplex.de

Tel +49(0)4451 - 9137-0

Fax +49(0)4451 - 81063

www.microplex.de

MICROPLEX® Printware AG



SPECIFICATIONS


The moderate investment as well as low operating costs guarantee an excellent price/performance ratio of the SOLID 32E.

With 600 dpi as standard, the SOLID 32E is also best suited for high-quality print-outs.

Technical Specifications

Print technology	Laser, OPC heat / pressure fixing	
Print speed	up to 32 pages/min (A4 landscape) 6,9 m/min	
Resolution	max. 600 dpi x 600 dpi	
Recommended monthly print volume	up to 200.000 pages (based on a using period of 60 months)	
Power supply	220V +/-10% / 50 Hz	
Acoustic noise (stand-by)	< 55 dB (A)	
Dimensions (WxDxH in mm)	609 x 609 x 419	
Environment	rel. h.	20 - 80 %
	temp.	10 - 31°C
Media	form length	3" - 33"
	form width	6,5" - 14,5"
	printable width	13,6"
	weight	60 - 160 g/m ²
Input	Push tractor	
Output	<i>Option</i>	Stacker Cutter

Straight Paper Path



Controller

Controller	MPC 5.x with Intel XScale PXA 255 (400 MHz-RISC-processor)	
Interfaces	Serial	USB, RS232, RS422
	Parallel	IEEE 1284
	LAN	Ethernet-Interface 10/100 MBit, bi-directional (TCP/IP)
Memory	RAM	64 MB
	Flash	16 MB
Emulations	MICROPLEX IDOL	IBM Proprinter
	HP PCL 5e	Diablo 630
	Epson FX-80	TIFF
		μ-Postscript
Optional Emulations	Printronix IGP	Magnum Code V
	PGL, EPL	Kyocera Prescribe
	Datamax, ZPLII	Express
	<i>(more emulations on request)</i>	
Barcodes	EAN 8, 13, 128, add on	Jetcaps (HP/SAP) Code 39
	2/5 3-stroke Datalogic	128 MSI
	2/5 3-stroke Matrix	UPC A, E
	Codebar, PDF 417	Postnet, KIX
Optional Barcodes	USD5 Datamatrix	UPS-Maxicode
	<i>(more barcodes on request)</i>	
Functions	Internal barcode generation on-the-fly in the printer	
	Intelligent form management Up to 12 MB flash for forms and fonts inside the printer	
	Format splitting in several subformats by command	
Optional Functions	Status out gives notice of each correctly printed page via interface	
	SPS - Control Integration of the printer into the production line, controlled by SPS-interface.	

Continuous Forms Laser Family



24
pages/minute

300
dpi

8,5"
print width



32
pages/minute

600
dpi

13,6"
print width



80
pages/minute
2up mode

300
dpi

17"
print width



Authorized MICROPLEX Partner:



MICROPLEX Printware AG

Panzerstraße 5
D-26316 Varel

Fon + 49(0)4451 - 9137-0
Fax + 49(0)4451 - 81063

Mail info@microplex.de

www.microplex.de



- Product names mentioned here in are trademarks and/or registered trademarks of their respective companies.
- All coloured and italic printed items are options.
- Technical specifications may be changed at any time without notice.
- All written numbers, prices and specification in this data sheet are for description purposes only. No promise or guarantee is made as to the accuracy of the numbers, prices or specification provided and furthermore no guarantee is provided that the numbers/prices quoted or specification given will be that of the final product purchased. It remains the duty of the buyer to confirm and prove that the specification provided in the product meets with the buyers needs regarding the buyers specific application and/or installation.