

T2024/9



“The” entry level Dot Matrix printer.

TallyGenicom's entry-level 9 pin, 80 column serial impact dot matrix printer is the T2024/9. This printer features very low running costs and considerable versatility with its optional roll paper holder.

Amongst the lowest priced matrix printers available this product features a comprehensive specification, including 300 characters per second maximum print speed, 6,000 pages per month workload, dual interfaces and industry standard emulations for versatile host connection.

The printer boasts advanced features such as automatic paper loading, parking, and top of form. It's unobtrusive with a small footprint, ideal for the desk, small office or the home. For draft printing its considerably less expensive running costs make it a viable alternative to low cost inkjet printers.

Mono Laser
Colour Laser
Production Ink
Dot Matrix
Line Matrix
Consumables

- Parallel and RS232 Serial interfaces as standard.
- IBM ProPrinter and Epson FX emulation's for easy connection on a wide variety of hosts.
- Automatic top of form for easy alignment.
- Paper park facility for easy alignment.
- Paper roll holder option.
- Small foot print.

T2024/9

Dot Matrix Printer

Features & Specifications

Printing technology	Serial impact dot matrix				
Printer types	Mono, 80 columns, 9-pin				
Workload	6,000 pages per month				
Advanced Automatic features	Paper loading, paper parking				
Print speed - std		Super Speed	Speed	Draft	NLQ
Characters per second	10 cpi			200	50
	12 cpi		240	200	60
	15 cpi	300			
Character pitch	10, 12, 15, 17.1, 20 cpi				
Line pitch	6, 8lpi, 1/216" line advance				
Fonts	Draft, copy draft, courier, sans serif, prestige, script, gothic download of 256 characters provided				
Paper handling - std	Tractor paper - rear push tractors with paper parking Cut sheet - Single sheet insertion (top)				
Paper handling - opt	Roll paper holder				
Paper types	Tractor paper 115 to 254mm max width Cut sheet 102 to 297mm max width Cut sheet 127 to 363mm max length				
Multi-part stationery	1+2 copies				
Interfaces - std	Serial RS232 and Parallel (Bi-directional) with 21Kb buffer				
Emulations - std	IBM ProPrinter II, Epson FX850				
Host Support includes	Windows operating environments, UNIX, SAP-R3, DOS, VMS and legacy systems				
Noise level (ISO 7779)	55dB(A)				
Power supply	230V 110/120V version available				
Print head life	100 million characters				
Consumables	Ribbon: 2.5 million characters				
Weight	3.3Kg				
Dimensions	(HxWxD): 110 x 380 x 287mm				
Reliability	MTBF: 6,000 hours				

NB: Paper is a highly variable medium, and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operating conditions.



 **TallyGenicom**[®]
> Power to Print

Rutherford Road, Basingstoke,
Hampshire, RG24 8PD.
Tel: UK 0800 652 4557
International: +44 (0) 1256 481 521
Fax: UK 0870 872 2889
Web: www.tallygenicom.co.uk