



MS180 Bar Code Scanner



Application

The Unitech MS180 is a reliable and affordable bar code scanner for retail, medical and light industry application.

Reliable yet Affordable

The MS180 Bar Code Scanner is a reliable yet affordable scanner.

The ergonomic design makes the scanning process easier and comfortable.

The MS180 is rugged designed to withstand multiple 5 feet drops to concrete.

Interface

The MS180 flexible, multiple interface design supports keyboard wedge, USB, RS232 and Wand emulation by simply replacing the cable.

The IBM PC XT/AT keyboard wedge interface supports different character sets.

Decoders

The MS180 is equipped with built-in decoder reads and discriminates all major symbologies, it helps you to reduce processing time and labor cost yet increase accuracy.

Warranty

The MS180 comes with Unitech premium 3 years warranty program of which the first year entitles user to a free one-on-one swapping. In the extended program this one-on-one swapping can be prolonged to 3 years.

Features & Benefits

- CCD Scanning for Reliability
- Ergonomic Design for Operator Comfort
- Multiple Interfaces for Compatibility
- Affordable Pricing
- Warranty program

► Performance

Scan rate: 33 scans / sec
Decode rate: 200 scans / sec
Printing contrast scale: Minimum 45 %
Resolution: 0.1 mm at contact, PCS = 45 %
Depth of field: PCS=90%
0 ~ 16 mm on 4/5/6/10/13 mils
0 ~ 25 mm on 40 mils
Width of field: 80mm
(PCS=90%, 1 mm codes, from 0 to 50 mm distance)
Scan angle: 30 ° ~ 150 °

► Functionality:

Operation modes: Trigger, Flash, Multi-scan, continuous and One Press one Modes
Interfaces: Keyboard wedge, USB, RS232, Wand emulation and TTL
Symbologies: Code 39 Standard and Full ASCII, Codabar, UPC/EAN with supplement codes, UCC/EAN128, Interleaved 2 of 5, MSI/Plessey code, Standard 2 of 5, China Postal, Code(Toshiba Code), Label Code IV and V, Delta Distance code, Code93, Code128, Code32(Italian Pharmacy).

► Optical

Receiving Device: 2160 Element linear imager
Light source: 660 nm visible red LED

► Electrical

Power supply: 5VDC \pm 5 %
Operating current: 100 \pm 5 mA @5V (Keyboard Wedge)
Standby current: 21 \pm 3 mA @ 5V (Keyboard Wedge)
Switch Life Time: Over 1million times micro switch
Beep Sound Volume: > 70dB
Connectivity: IBM PC XT/AT or comparable, PS/2, Notebook, MAC and other common terminals

► Mechanical

Housing material: 30%PC + 70% ABS, UL94U0
Outline shape: Steamline Handy Type with Unitech logo
Connector type: RJ-45 phone jack
Weight: 125g (w/o cable)
Dimension: L 190 x W 88 x H 50 mm

► Environmental

Operating temperature: 0° C ~ 50° C
Storage temperature: -20° C ~ 60° C
Relative humidity: 20% RH ~ 85% RH
ESD protection: 8KV contact, 12KV Air discharge
Mechanical shock: 1.5 M to concrete (10 times)
Safety Approval: CE, FCC Class A, BSMI

► Models

MS180-1K	MS180 CCD Scanner including Keyboard wedge
MS180-1R	MS180 CCD Scanner including RS232 cable
MS180-1U	MS180 CCD Scanner including USB cable
MS180-1W	MS180 CCD Scanner including wand emulation cable

► Accessories

MS201	Desktop holder for MS180
-------	--------------------------



MS180-06V5

UNITECH EUROPE is the head office for EMEAKapitein Hatterasstraat 19
5015 BB Tilburg, The NetherlandsTel: +31.13.460 9292
Fax: +31.13.460 9293www.unitech-europe.come-mail: sales@unitech-europe.nl**Unitech Electronics (Headquarter) Taipei, Taiwan**www.unitech-adc.com

Specifications subject to change without notice. Copyright Unitech Europe. All rights reserved.

Unitech is a registered trademark of Unitech Electronics Co., Ltd. All trademarks are the property of their respective owners.